

The



Company

"THE FLUX IS

IN THE FLAME"

440 365-1941
FAX 440 365-3495

32 Hawthorne Street
P.O. Box 1170
Elyria, Ohio 44036-1170
www.gasflux.com

LIQUID GASFLUX – TYPE MB

A water-white volatile liquid. Principal ingredient $B(OCH_3)_3$. Is non-corrosive and can be handled in mild steel or copper equipment.

ANSI /AWS A5.31 Type FB3-K

Properties;

| | |
|-------------------------|----------------------|
| Boiling Point | 58.0 – 66.8°C |
| Flash Point | -5°C |
| Specific Gravity | .880 - .890 |
| Borate Content | 72 – 75% (by weight) |
| Water Content | less than .5% |
| Distillation to Dryness | Residue nil |
| Net Weight per Gallon | 7.36 lbs. |

Classifications;

Flammable Liquid N.O.S.
(Contains; Trimethyl borate and Methanol)
UN1993
Packing Group II, Class 3
Schedule B Number 3810.90.0000

Packing and Shipping;

53 Gallon (200.6 liter) non-returnable UN certified steel tighthead drums, 425 lbs each.

5 Gallon (18.93 liter) non-returnable UN certified steel tighthead drums, 43 lbs each.

1 Gallon (3.78 liter) non-returnable UN certified plastic bottles, sold individually or in a 4 pack carton.

